

Model		GJC12AB-E1RNB9A		GJCR18ADNK1B9A		GJC24AC-E1RNB9A	
Function		COOLING	HEATING	COOLING	HEATING	COOLING	HEATING
Rated Voltage		230V		230V		230V	
Rated Frequency		50Hz		50Hz		50Hz	
Total Capacity (W)		3500	/	5280	/	6300	/
Power Input (W)		1300	/	1980	/	2400	/
Rated Input (W)		1770	/	2750	/	3250	/
Rated Current (A)		12	/	13.2	/	15.7	/
Air Flow Volume (m3/h) (H/M/L)**		520		730		1000	
Dehumidifying Volume (l/h)		0.8		2.0		2.4	
EER / C.O.P (W/W)		2.6		2.66		2.6	
Energy Class		/		/		/	
Indoor Side	Fan Type - Piece	Cross flow fan – 1		Cross flow fan–1		Cross flow fan–1	
	Diameter - Length (mm)	φ222X90		φ205X110		φ224X110	
	Evaporator	Aluminum fin-copper tube		Aluminum fin-copper tube		Aluminum fin-copper tube	
	Pipe Diameter(mm)	φ7		φ7		φ7	
	Row-Fin Gap	2-1.3		2-1.3		2-1.3	
	Coil length (l) x height (H) x width (L)	330X323.9X25.4		422X381X25.4		422X381X25.4	
	Swing Motor Model	MP24VA		SM020B		MP28ED	
	Output of Swing Motor (W)	2.5		4		1.5	
	Fuse (A)	/		0.02		0.02	
	Sound Pressure Level dB (A) (H/M/L)	54/50/48		52/50/48		62/60/58	
	Sound Power Level dB (A) (H/M/L)	64/60/58		62/60/58		72/70/68	