

Model			GVA36AH- M3NNA5A	GVA48AH-M3NNA5A	GVA60AD-M3NNA2A
Function			Cooling/Heating	Cooling/Heating	Cooling/Heating
Capacity	Cooling	W	11,000	12,400	16,000
	Heating	W	12,700	13,600	18,000
EER/C.O.P		W/W	2.81/3.01	2.51/2.81	2.5/2.9
Power Supply		Ph,V,Hz	3Ph,380-415V,50HZ		
Power Input	Cooling	W	3920	4940	6400
	Heating	W	4220	4840	6200
Rated Current	Cooling	A	6.67	8.40	12.05
	Heating	A	7.18	8.24	12.05
Indoor Unit					
Airflow Volume	Indoor	m3/h	1700	1,800	2,000
Sound Pressure Level	Indoor	dB(A)	51/49/47/45	52/50/48/46	58/53/50
Outline Dimension	WxHxD	mm	518X1870X395	518X1870X395	540/1750/380
Package Dimension	LxWxH	mm	738X533X2095	738X533X2095	720X515X2000
Net Weight/Gross Weight	Indoor	kg	60/86	63/89	60/85
Outdoor Unit					
Sound Pressure Level	Outdoor	dB(A)	59	59	63
Piping Connection	Gas	mm	Ø 19	Ø 19	Ø19
	Liquid	mm	Ø 12	Ø 12	Ø 12
Outline Dimension	WxHxD	mm	1032X1250X412	1032X1250X412	950X1250X412
Package Dimension	LxWxH	mm	1113X453X1295	1113X453X1295	1110X450X1280
Net Weight/Gross Weight	Outdoor	kg	105/116	110/121	115/126
Loading Quantity					
Loading Quantity	40'GP	sets	35	35	41
	40'HQ	sets	41	41	47